



MODEL 6600



Pitot Static Tester: 3 - Outputs

See Reverse for Specifications

Model 6600 Automated Pitot Static Tester with 3 Outputs

The 6600 Automated Tester is designed to connect directly to an aircraft's Pitot and Static system. The tester has one Static output, one Pitot output and a third Differential output. Each output has two ports for easy hose connections. Using the small and light-weight Remote unit a user can operate the tester from the cockpit and use it to test the entire pitot and static system of the aircraft, including altimeters, climb indicators, airspeed / Mach indicators, air data computers and auto-pilots. The tester includes built-in vacuum and pressure pumps and emergency manual bleed-down valves. The high accuracy of this unit meets the latest RVSM requirements. Also, it requires no maintenance other than to be calibrated only once a year. The use of "Profiles" makes it possible for the operator to run through a test using only a single key on the Remote unit.

Specifications

Static Output

Pressure function

range:	0.1 to 42 inHg
resolution:	0.001 inHg
accuracy:	0.002 inHg

Altitude function

range:	-4000 ft. to 60,000 ft.
resolution:	1 foot
accuracy:	2 ft. @ 0 ft. 6 ft. @ 35,000 ft. 12 ft. @ 50,000 ft.

Climb function

range:	0 ft/min to 25,000 ft/min
resolution:	1 ft/min
accuracy:	1% of rate of climb

Pitot Output

Pressure function

range:	0.1 to 60 inHg
resolution:	0.001 inHg
accuracy:	0.003 inHg

Airspeed function

range:	0 to 650 knots
resolution:	0.1 knots
accuracy:	0.5 knots @ 50 knots 0.25 knots @ 100 knots 0.05 knots @ 650 knots

Mach function

range:	0.0 to 3.0 Mach
resolution:	0.001 Mach
accuracy:	0.001 above 0.2 Mach

Differential Output (referenced to Static) (Secondary Static Output)

range:	+/- 30.0 inHg
resolution:	0.001 inHg
accuracy:	0.002 inHg

"Jog" feature

Allows set-point to be increased or decreased in steps of 1 foot or 0.1 knots simply by using arrow keys.

"Profiles" feature

A profile of the standard set-points of an altimeter check or airspeed check can be downloaded from a computer. Such a profile allows the user to operate the unit using a single key. Up to 20 such profiles can be stored in the unit. PC-based software is included.

Pressure & Vacuum system

The tester includes separate pressure and vacuum diaphragm pumps for higher reliability. The pressure system includes a membrane dryer, and a filter to provide clean dry air for the entire system.

Remote unit

The Remote unit is the operator interface for the tester. It is small and light enough to be used in the cockpit. The tester can be turned On and Off from the Remote. All valid parameters, including altitude, climb and airspeed, are clearly displayed simultaneously on a single screen on the Remote.

Manual Vent

The tester includes manual metering valves to enable the system (aircraft) to be manually vented in the event of loss of power.

Power requirement

90-260 VAC, 47-440 Hz ; 200 W

Interfaces

RS232 ; IEEE-488 & Encoder optional

Dimensions & weights

Main unit: 22" x 14" x 9" / 40 lbs

Remote unit: 7" x 8" x 2" / 1 lb.

Environmental specs:

Operating temp. 0° to 50°C

Storage temp. -25° to 75°C

Humidity: 5 to 95% non-condensing

Specifications subject to change without notice

5/07



Houston, TX
USA

Phone: (800) 285-7337
(281) 568-8394
Fax: (281) 568-8399
Website: www.laversab.com
E-mail: sales@laversab.com